DUCHESNE COUNTY MONUMENT SURVEY RECORD R4W T3S DISTANCE LINE SEC 8 | SEC 9 N 76°14'51" W N 00°01'31" W 102.01 L1 SEC 17 | SEC 16 24.90 S 63°48'05" E 36.98 L3 S 02°54'42 20.17 L4 U.S.B.&M. R-9NAIL AND WASHER ON LEFT SIDE OF RR TIE FENCE CORNER NAIL AND WASHER ON LEFT SIDE OF RR TIE GATE POST 8 41 5000 SOUTH STREET N 89°24'29" E 2667.53 N 89°17'50" E 2670.52

NAIL AND WASHER
ON LEFT SIDE OF
RR TIE FENCE
CORNER

NOTE:
THE BASIS OF BEARINGS IS GEODETIC NORTH
DERIVED FROM G.P.S. OBSERVATIONS AT A
CONTROL POINT (TOWNSHIP CORNER)
LOCATED AT LAT. 40°15'22.90258''N AND
LONG. 110°23'21.19760''W USING THE UTAH
STATE G.P.S. VIRTUAL REFERENCE STATION
CONTROL NETWORK MAINTAINED AND
OPERATED BY THE AUTOMATED GEOGRAPHIC
REFERENCE CENTER

PAVED COUNTY ROAD

DESCRIPTION OF CORNER EVIDENCE FOUND

ĆOR

FOUND DUCHESNE COUNTY 2½" DIA. ALUMINUM CAP ON 5/8" REBAR SET IN CONCRETE COLUMN AT QUARTER CORNER

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

REFERENCED TO ADJACENT QUARTER CORNERS, AS WELL AS REFERENCE POINTS SHOWN



NAIL AND WASHER ON LEFT SIDE OF POWER POLE ĆOR

30 '

NORTH

SCALE: 1"=30'

0'

MARKINGS ON MONUMENT

STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET) NAD83 UTAH CENTRAL ZONE

N: 7253717.295 E: 1961209.383 NAVD88 ELEV: 5931.06'

LATITUDE: 40°13'39.63080" N LONGITUDE: 110°21'03.71808" W ELLIPSOID HEIGHT: 5875.18'

(GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

UT300010S0010W0_200140




PHOTO OF MONUMENT FACING EAST

CERTIFICATION

I <u>Jerry D. Allred</u>, Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date _____II DEC '17

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

